



Walter Turn PSSN



- gamme de porte-outils négatifs
- usinage extérieur
- serrage par levier

Outil			h = h ₁ mm	b mm	f mm	f ₁ mm	l ₁ mm	l ₄ mm	l ₂₀ mm	γ	λ _s	Type	
κ = 45°			12	20	20	25	16,7	125	28	133,3	-8°	0°	SN..1204..
			12	25	25	32	23,7	150	28	158,3	-8°	0°	
			12	32	25	32	23,7	170	29	178,3	-8°	0°	
			15	25	25	32	21,8	150	32	160,2	-8°	0°	SN..1506..
			15	32	32	40	29,8	170	32	180,2	-8°	0°	
			19	32	32	40	27,5	170	37,5	182,5	-8°	0°	SN..1906..



Mesuré à l'aide de la plaquette étalon SN .. 120408 / SN .. 150612 / SN .. 190612.

Informations relatives à l'angle de coupe γ (pour les plaquettes amovibles sans brise copeaux) et à l'angle d'inclinaison λ_s, voir page A 301.

La désignation des outils comprend le corps ainsi que les pièces de rechange sans les plaquettes.

Pièces de rechange	Type h mm	SN..1204.. 20-32	SN..1506.. 25-32	SN..1906.. 32
	Sous cale pour	AP141-SN1216 r ≤ 1,6	AP142-SN1524 r ≤ 2,4	AP143-SN1924 r ≤ 2,4
	Levier	KN102	KN104	KN106
	Vis de serrage Couple de serrage	FS352 (SW 3) 5,0 Nm	FS354 (SW 3) 5,0 Nm	FS356 (SW 4) 10,0 Nm
	Goupille tubulaire	RS102	RS103	RS104
	Poinçon	MD101	MD102	MD102
	Clé soudée	ISO 2936-3 (SW 3)	ISO 2936-3 (SW 3)	ISO 2936-4 (SW 4)

Accessoires	Type h mm	SN..1204.. 20-32	SN..1506.. 25-32	SN..1906.. 32
	Sous cale pour	AP141-SN1208 r ≤ 0,8	AP142-SN1516 r ≤ 1,6	AP143-SN1912 r ≤ 1,2

