


Alésoir machine avec cône morse

F4142

H7




- HSS-E - non revêtu
- forme A
- coupe à droite - à goujures droites

	P	M	K	N	S	H	O
non revêtu	●●		●●	●●			●●

DIN 208

Cône morse



D _c mm	L _c mm	l ₁ mm	MK	Z	Désignation F4142
5	23	133	MK1 B	6	-5
6	26	138	MK1 B	6	-6
7	31	150	MK1 B	6	-7
8	33	156	MK1 B	6	-8
9	36	162	MK1 B	6	-9
10	38	168	MK1 B	6	-10
11	41	175	MK1 B	6	-11
12	44	182	MK1 B	6	-12
13	44	182	MK1 B	6	-13
14	47	189	MK1 B	8	-14
15	50	204	MK2 B	8	-15
16	52	210	MK2 B	8	-16
17	54	214	MK2 B	8	-17
18	56	219	MK2 B	8	-18
19	58	223	MK2 B	8	-19
20	60	228	MK2 B	8	-20
21	62	232	MK2 B	8	-21
22	64	237	MK2 B	8	-22
23	66	241	MK2 B	8	-23
24	68	268	MK3 B	8	-24
25	68	268	MK3 B	8	-25
26	70	273	MK3 B	8	-26
27	71	277	MK3 B	10	-27
28	71	277	MK3 B	10	-28
29	73	281	MK3 B	10	-29
30	73	281	MK3 B	10	-30
31	75	285	MK3 B	10	-31
32	77	317	MK4 B	10	-32

