


Fraise à copier hémisphérique Protostar® 30



Matériaux jusqu'à 48 HRC



- carbure monobloc
- 2 arêtes de coupe
- avec coupe au centre
- angle d'hélice de 30°

	P	M	K	N	S	H	O
non revêtu				••			
TAX	••	•		•			

DIN 6527 L	D _c h7 mm	R mm	L _c mm	l ₁ mm	l ₄ mm	d ₁ h5 mm	Z	Désignation non revêtu H800111	Désignation TAX H8001118
Queue DIN 6535 HA	1	0,5	3	38	10	3	2	-1	-1
	1,5	0,75	3	38	10	3	2	-1.5	-1.5
	2	1	6	38	10	3	2	-2	-2
	2,5	1,25	7	38	10	3	2	-2.5	-2.5
	3	1,5	7	38	10	3	2	-3	-3
	4	2	8	57	21	6	2	-4	-4
	5	2,5	10	57	21	6	2	-5	-5
	6	3	10	57	21	6	2	-6	-6
	7	3,5	13	63	27	8	2	-7	-7
	8	4	16	63	27	8	2	-8	-8
	9	4,5	16	72	32	10	2	-9	-9
	10	5	19	72	32	10	2	-10	-10
	12	6	22	83	38	12	2	-12	-12
	14	7	22	83	38	14	2	-14	-14
	16	8	26	92	44	16	2	-16	-16
	18	9	26	92	44	18	2	-18	-18
	20	10	32	104	54	20	2	-20	-20

Queue DIN 6535 HA

