


# Fraise à copier hémisphérique Protostar® HSC 30 Ultra




Matériaux avec une dureté comprise entre 48 et 63 HRC



- carbure monobloc
- grande longueur
- 2 arêtes de coupe
- avec coupe au centre
- angle d'hélice de 30°

	P	M	K	N	S	H	O
TAX						●●	

DIN 6527 L	D <sub>c</sub> h7 mm	R mm	L <sub>c</sub> mm	l <sub>3</sub> mm	d <sub>2</sub> mm	l <sub>1</sub> mm	l <sub>4</sub> mm	d <sub>1</sub> h5 mm	Z	Désignation TAX H8004028
Queue DIN 6535 HA	5	2,5	5	20	4,9	57	21	6	2	-5
	6	3	6	24	5,9	63	27	8	2	-6
	8	4	8	29	7,85	72	32	10	2	-8
	10	5	10	35	9,85	83	38	12	2	-10
	12	6	12	36	11,8	83	38	12	2	-12
	16	8	16	42	15,8	92	44	16	2	-16



Norme P, L	D <sub>c</sub> h7 mm	R mm	L <sub>c</sub> mm	l <sub>3</sub> mm	d <sub>2</sub> mm	l <sub>1</sub> mm	l <sub>4</sub> mm	d <sub>1</sub> h5 mm	Z	Désignation TAX H8004128
Queue DIN 6535 HA	6	3	6	-	-	57	21	6	2	-6-57
	6	3	6	-	-	80	44	6	2	-6-80
	8	4	8	-	-	63	27	8	2	-8-63
	8	4	8	-	-	100	64	8	2	-8-100
	10	5	10	-	-	72	32	10	2	-10-72
	10	5	10	-	-	100	60	10	2	-10-100
	12	6	12	-	-	83	38	12	2	-12-83
	12	6	12	-	-	100	55	12	2	-12-100
	16	8	16	-	-	125	77	16	2	-16-125

