


Fraise à queue Protostar® N 45 Compact



Matériaux jusqu'à 48 HRC




- carbure monobloc
- 3 arêtes de coupe
- avec coupe au centre
- angle d'hélice de 45°


Particularités :

Rainurage : $a_p \leq 0,5 \times D_c$

Dressage : $a_e \leq 0,6 \times D_c$

	P	M	K	N	S	H	O
TAX	●●	●	●	●	●	●	●

Norme P, S	D_c	L_c	l_1	l_4	d_1	Z	Désignation TAX H3013018
	h11 mm				h6 mm		
Queue DIN 6535 HA	2	3	39	12	6	3	-2
	3	4	39	12	6	3	-3
	4	5	39	12	6	3	-4
	5	6	39	12	6	3	-5
	6	7	39	12	6	3	-6
	8	9	44	17	8	3	-8
	10	11	51	20	10	3	-10
	12	13	56	22	12	3	-12

DIN 6527 K	D_c	L_c	l_1	l_4	d_1	Z	Désignation TAX H3013118
	h11 mm				h6 mm		
Queue DIN 6535 HA	2	6	50	14	6	3	-2
	3	7	50	14	6	3	-3
	4	8	54	18	6	3	-4
	5	10	54	18	6	3	-5
	6	10	54	18	6	3	-6
	8	16	58	22	8	3	-8
	10	19	66	26	10	3	-10
	12	22	73	28	12	3	-12